

**15" TFT monitor for the
NCR SelfServ series**



Series: TFT-15-GAA

This 15" monitor is in standard type (LED) available and was developed for following NCR ATM systems:

6622 / 6625 / 6626 / 6628 / 6631 / 6632 / 6634 / 6636

- Ø Long life cycle due to energy-saving LED technology
- Ø Easy installation by Plug & Play

Technical Data

TFT-15-GAA

Display:

Display size
Brightness
Resoluton timings
Contrast

Standard:
15"
400 cd/m² (LED)
max. 1024 x 768 dots
500 : 1

Input Signal:

Videonorm
H. Frequency
V. Frequency
Sync. signal
Pixelclock
Colours

VGA RGB analog
31 - 35 kHz
50 - 75 Hz
H/V seperated, TTL level
max. 30 MHz
6 bit per colours

Adjustments (OSD):

Brightness, Contrast, Horizontal position, Vertical Position,
Default; Settings saved automatically

Power Management:

Background lighting is switched off by missing video signal.

Connections:

Input signal
Power supply
Power consumption

VGA / DVI
12 - 24V DC mini fit connector from ATM
5 W

Operation conditions:

Operating temperature 0°C - + 65°C

MTBF:

Background lighting 50.000 hours / 25°C

Weight:

4,5 Kg (9.5 lbs)

Manufactured acc. to:

CE: EN60950 conform

Scope of delivery:

15" monitor chassis

Warranty:

24 month

Versions:

NCR SelfServ	ReTecCom-Standard
66xx 15"	015-N0-R10-SELF



Date: 04/2011